

## 2 Watt CW Test Transmitter

This 2 Watt PST transmitter is a complete, portable CW test source capable of transmitting a test signal between 698 and 960 MHz. The RF output level can be adjusted between +10 and +33 dBm in 0.1 dB steps.

The frequency and output level can be set from the touch keys on the front panel. The status can be easily monitored from the backlit LCD display. The transmitter also contains a USB interface enabling the user to download specific transmitter configurations stored on a PC or control the transmitter remotely.

The transmitter can be powered using the internal 6 AA rechargeable batteries for 1.5 hours of continuous operation at 2 W, 2 hours at 1 W, or 5 hours at +10 dBm. Or it can be operated with the AC/DC wall adapter included.



- **Calibrated RF output level**
- **Use as a test source to evaluate indoor and outdoor wireless coverage**

- 698-960 MHz
- 10, 12.5, 30, & 200 kHz, 1.25 MHz step size
- Programmable output frequency and amplitude
- Fully independent user interface & touch screen display
- +10 to +33 dBm output level
- SMA or N-type female connector
- Portable (4 lbs.)
- Battery operated
- Optional durable vinyl carrying case

Pricing		
2 Watt PST	310-010029-004	\$4,395.00
Soft-sided Case	380-010195-001	\$95.00

(217) 897-1744

[www.praxsym.com](http://www.praxsym.com)